



AZ15ZVRK-M16

- Long life
- Multiple coding
- Double-insulated
- 52 mm x 75 mm x 30 mm
- Insensitive to soiling
- Thermoplastic enclosure
- Large wiring compartment
- 3 cable entries M 16 x 1.5
- Slotted holes for adjustment, circular holes for location
- High level of contact reliability with low voltages and currents

Data

Ordering data

Product type description	AZ 15 ZVRK
Article number (order number)	101153619
EAN (European Article Number)	4030661169354
eCl@ss number, Version 9.0	27-27-26-02

Approval - Standards

Certificates	TÜV
	cULus
	CCC
	EAC

General data

Product name	AZ 15
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Material of the contacts, electrical	Silver
Gross weight	100 g

General data - Features

higher Latching force	Yes
Suitable for elevators	Yes
Number of safety contacts	1

Safety appraisal

Standards	BG-GS-ET-15 ISO 13849-1 EN 60947-5-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	2,000,000 Operations
-----------------------------------	----------------------

Mechanical data

Mechanical life, minimum	1,000,000 Operations
Latching force	30 N
positive break travel	8 mm
Positive break force, minimum	10 N
Actuating speed, maximum	2 m/s

Mechanical data - Connection technique

Terminal Connector	Screw connection
Cable section, minimum	0.25 mm ²
Cable section, maximum	2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.

Mechanical data - Dimensions

Height of sensor	75 mm
Length of sensor	30 mm
Width of sensor	52 mm

Ambient conditions

Protection class	IP 67 to IEC/EN 60529
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+80 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	6 kV
---------------------------------	------

Electrical data

Thermal test current	10 A
Switching element	Opener (NC)
Switching principle	Creep circuit element

Product picture (catalogue individual photo)



ID: kaz15f01


| 105,9 kB | .png | 74.083 x 100.189 mm - 210 x 284

Pixel - 72 dpi

| 409,7 kB | .jpg | 168.981 x 228.6 mm - 479 x 648

Pixel - 72 dpi

Dimensional drawing basic component



ID: 1az15g01

| 39,6 kB | .cdr |


| 61,6 kB | .jpg | 352.778 x 245.181 mm - 1000 x 695

Pixel - 72 dpi

| 3,1 kB | .png | 74.083 x 51.506 mm - 210 x 146 Pixel

- 72 dpi

Switch travel diagram



ID: kaz15s01

| 33,3 kB | .jpg | 352.778 x 60.325 mm - 1000 x 171

Pixel - 72 dpi

| 19,1 kB | .cdr |

| 1,5 kB | .png | 74.083 x 12.7 mm - 210 x 36 Pixel

- 72 dpi

Diagram



ID: k1o--k01

| 20,8 kB | .jpg | 352.778 x 53.622 mm - 1000 x 152

Pixel - 72 dpi

| 16,8 kB | .cdr |

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 25.11.2020 16:19:38