

1) Optical axis receiver, 2) Optical axis emitter, 3) Operating voltage, 4) Light reception



IND. CONT. EQ  
 4R97  
 for use in the secondary of  
 a class 2 source of supply



## Basic features

Approval/Conformity	CE cULus WEEE
Basic standard	IEC 60947-5-2
Principle of operation	Photoelectric sensor
Reference reflector	BOS R-9
Series	R020K
Style	Square Connection 60°

## Display/Operation

Display	LED green: Power LED yellow: Light received
---------	--

## Electrical connection

Cable diameter D	2.40 mm
Cable length L	2 m
Conductor cross-section	0.09 mm <sup>2</sup>
Connection	Cable, 2.00 m, PVC
Number of conductors	3
Polarity reversal protected	yes
Short-circuit protection	yes

## Electrical data

No-load current $I_0$ max. at $U_e$	20 mA
Operating voltage $U_b$	10...30 VDC
Protection class	III
Rated insulation voltage $U_i$	50 V DC
Rated operating current $I_e$	50 mA
Rated operating voltage $U_e$ DC	24 V
Ripple max. (% of $U_e$ )	20 %
Switching frequency	800 Hz
Turn-off delay $t_{off}$ max.	0.63 ms
Turn-on delay $t_{on}$ max.	0.63 ms
Voltage drop $U_d$ max. at $I_e$	2.5 V

## Environmental conditions

Ambient temperature	-25...50 °C
Protection degree	IP67

## Functional safety

MTTF (40 °C)	3487 a
--------------	--------

## Material

Housing material	ABS
Material jacket	PVC
Material sensing surface	PMMA

## Mechanical data

Dimension	7.7 x 26.8 x 13.5 mm
Mounting	Screw M3

Photoelectric Sensors  
**BOS R020K-PO-PR11-02**  
Order Code: BOS020Y

# BALLUFF

## Optical features

Ambient light max.	5000 Lux
Blind zone	25 mm
Light spot size	Ø 11 mm at 250 mm
Light type	LED, red light
Polarizing filter	yes
Principle of optical operation	Retroreflective sensor
Switching function, optical	Light-on

Wave length 660 nm

## Output/Interface

Switching output PNP normally closed (NC)

## Range/Distance

Range 0...3 m  
Rated operating distance  $S_n$  3 m

## Remarks

The sensor is functional again after the overload has been eliminated.

Actuation object (target): gray card, 200 x 200, 90 % remission, lateral approach, approach direction vertical to lens axis plane.


For additional information, refer to user's guide.

Order accessories separately.

For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

## Wiring Diagrams



## Opto Symbols

