

SIMATIC DP, PM-E power modules for ET 200S; 24 V DC with diagnostics



Supply voltage

Load voltage L+

- | | |
|-------------------------------|--|
| • Rated value (DC) | 24 V |
| • Short-circuit protection | No; external (e.g. automatic circuit breaker), tripping characteristic C |
| • Reverse polarity protection | Yes |

Input current

from load voltage L+ (without load), max.	4 mA
---	------

Current carrying capacity

up to 60 °C, max.	10 A
-------------------	------

Power loss

Power loss, typ.	0.1 W
------------------	-------

Interrupts/diagnostics/status information

Diagnoses

- | | |
|------------------------|-----|
| • missing load voltage | Yes |
|------------------------|-----|

Diagnostics indication LED

- | | |
|----------------------------------|-----|
| • Rated load voltage PWR (green) | Yes |
|----------------------------------|-----|

- Group error SF (red)

Yes

Parameter

Remark	3 byte
missing load voltage	Disable / enable

Potential separation

primary/secondary	Yes; between rated load voltage and backplane bus, between power modules
-------------------	--

Isolation

Isolation tested with	500 V DC
-----------------------	----------

Dimensions

Width	15 mm
Height	81 mm
Depth	52 mm

Weights

Weight, approx.	35 g
-----------------	------

last modified: 11/28/2020